

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate no.:
MEDB0000144
Revision no.:
2

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

This is to certify:

that the **Fire doors**

with type designation(s)
AM B-15 Fire Door dB(DL)

issued to

Antti-Teollisuus Oy
Kanunki, Finland

is found to comply with the Implementing Regulation **(EU) 2025/1533** for
Item no. **MED/3.16** (Row 1 of 1)
according to the following requirements:
IMO MSC.1/Circ.1511, SOLAS 74 Reg. II-2/9.


Further details of the equipment and conditions for certification are given overleaf.

Date of issue: **2025-12-05**

Expiry date: **2030-12-04**

DNV local unit:
Finland CMC

Approval Engineer:
Tessa Biever



Notified Body
no.: **0575**

for DNV AS



Digitally Signed By:
Christine Mydlak-Röder
Christine Mydlak-Röder
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment signed 17 October 2005, and amended by Decision No 1/2023 dated August 21st, 2023.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.



Product description

"AM B-15 Fire Door dB(DL)"

A door combination comprised of two doors mounted in series in separate frames where the door on the unexposed side opens away from the fire and the door on the exposed side opens towards the fire. Both door leaves are constructed from an insulation core consisting of 2 layers of 12 mm stone wool slabs 'SeaRox SL488' (density 220 kg/m³, manufactured by Rockwool) and one layer of 8 mm glass wool 'Isover KH' (density 20 kg/m³, manufacturer by Saint Gobain). On both sides of the insulation core a 0.7 mm perforate steel is fixed by means of an adhesive. Gap between the two door leaves is 39 mm. Each door leaf has three hinges and a lock.

The thickness of one door leaf is 32 mm.

For further details, see drawings listed under Type Examination documentation.

Application/Limitation

Approved for use as an integrated part of fire retarding divisions of class B-15.

Maximum door leaf size: 832.7 mm x 2064 mm (W x H)

Maximum clear door opening: 800 mm x 2052 mm (W x H)

The insulation materials and adhesives used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity. This requirement may also be applicable for surface materials used, if required by relevant rules and regulations.

A fire door of marginally larger dimensions than a fire-tested fire door may be individually assessed and accepted by Flag Administration (or Recognized Organization acting on its behalf) for a specific project with the same classification, provided documented compliance with IMO MSC.1/Circ.1319.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Document No.	Rev.	Title
EUF129-25000271- T1		Test report dated 19 September 2025 from Eurofins, Espoo, Finland.

Tests carried out

Tested according to IMO 2010 FTP Code part 3.

The door has been successfully tested for extended test period of 26 minutes for insulation and 37 minutes for integrity.

Marking of product

The product is to be marked with name and address of manufacturer, type designation, fire technical rating, the Mark of Conformity and USCG approval number if applicable (see first page).